SONY

TC-WA7ESA

Dual Auto Reverse Cassette

Key Features

- Dual Auto Reverse Cassette Deck
- Relay Play
- Automatic record calibration
- Automatic record level
- Twin linear time counters
- Power supply wit FET buffer
- Dolby® S, B and C noise reduction systems
- Dolby HX Pro® circuitry
- High-speed dubbing
- Two 2-motor transports

ES

TC-WA7ESA

Dual Auto Reverse Cassette

Features

Key Features

Dolby HX Pro
Dolby B and C noise reduction
Dolby S-Type Noise Reduction
Dual Auto Reverse Decks
Five-year limited warranty
Remote capable
Gold-plated headphone jack
High-speed Fast Forward and Rewind
Record Mute
Auto Play
Record level
Fader switch
14-segment fluorescent peak level meters
Multiple AMS Track Search
RMS Track programming
Twin Linear Time Counters
Relay Play
Full logic feather-touch transport controls
Power supply with FET buffer
Switchable MPX Filter
High-density Permalloy heads
Automatic Record Calibration
Automatic Record Level
Two ultra-stable 2-motor transports
High-speed dubbing

Specifications

Audio

Output Level and Impedance: Line: 0.5V, 47kohms; Headphone: 0.25mW, 32 ohms
Input Sensitivity/Impedance: 0.16V, 47kohms
Harmonic Distortion: Type I: 0.4% @ 315Hz; Type IV: 1.8% @ 315Hz
Wow and Flutter: 0.07% WRMS
Signal-to-Noise Ratio: Type I, Dolby® NR off: 55dB; Type II, Dolby® NR off: 57dB; Type IV, Dolby® NR off: 58dB
Frequency Response: Type I: 30 - 16,000Hz, ±3dB; Type II: 30 - 17,000Hz, ±3dB; Type IV: 30 - 19,000Hz, ±3dB

General

Power Consumption: 26W

TC-WA7ESA

Weight

9 lbs, 4 oz (4.2 Kg)

Dimensions (WHD)

17 x 4 3/4 x 11 1/2" (432 x 121 x 292mm)

UPC Code

0272425044310